

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

**2649-CPR-26001301**

## CE CONFORMITY

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product(s)

**Product(s) Reference:** Single Leaf Single Action Swing Wooden Door  
**Intended use:** Fire/smoke compartmentation and/or escape routes  
**Product(s):** GUANGDONG YOHOME - CE Wooden Fire Doorset (model YHCEFD90) - CE  
Spec ID: 91664  
Listing Information: See following page(s)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):  
**EN 14351-1:2006+A2:2016/ EN 16034:2014**

**Placed on the Market under the name of:** Guangdong Yohome Door Co., Ltd.  
Room 1101, 11th Floor, Ruiheng Science and Technology Innovation Park  
No. 20 Juyuan South Road, Guicheng Sub-district, Nanhai District  
Foshan, Guangdong 528299  
China

**And produced in the manufacturing plant:** 5029350

Under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product

This certificate was first issued on May 15, 2026 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods, nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

*The issued document and statement(s) herein makes reference only to a presumption of conformity in accordance with the CPR Regulations EU 305/2011 (as amended). However, it is the manufacturer's or their authorised representative's sole responsibility to affix the CE logo and, by doing so, confirms full compliance and conformity to all other European mandatory directives and regulations that may also apply*



**Notified Body**  
**NB 2649**

**Signature:**

**Initial registration Date:** May 15, 2026

**Name:** Pedro Cabezuelo del Pozuelo  
**Position:** Certification Manager NB

**Expiration Date:** December 31, 2026  
**Issue Status:** 1

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

## LISTING INFORMATION

### Product Description:

Single Leaf Single Action Swing Wooden Fire Door with Glazed Panel and Wooden Frame Assembly

Under **System 1** for the performances set out in this certificate are applied and that the performance of the construction product fulfills all the prescribed requirements as per TABLE 1 and TABLE 2.

Product Name: CE Wooden fire doorset

Model Ref: YHCEFD90

Brand: YOHOME

**TABLE 1. ZA.1 Clauses for external pedestrian doorsets from GUANGDONG YOHOME DOOR CO., LTD.**

| Product: External pedestrian doorsets by the scope of EN 14351-1. |                                                                                                                |                                                   |
|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
| Intended uses: Fire/smoke compartmentation and escape routes.     |                                                                                                                |                                                   |
| Essential Characteristics                                         | Requirement clauses                                                                                            | Results                                           |
| Resistance to wind load                                           | Load-bearing capacity and deflection against wind                                                              | NPD                                               |
| Resistance to snow and permanent load                             | Load-bearing capacity against snow and permanent load                                                          | NPD                                               |
| Reaction to fire                                                  | Reaction to Fire performance in accordance with EN 13501-1                                                     | NPD                                               |
| External fire performance                                         | External Fire performance in accordance with EN 13501-5                                                        | NPD                                               |
| Watertightness                                                    | Watertightness performance in accordance with EN 12208                                                         | NPD                                               |
| Dangerous substance                                               | Release dangerous substances                                                                                   | No dangerous substances declared for this product |
| Impact resistance                                                 | Impact resistance in accordance with EN 13049                                                                  | NPD                                               |
| Load bearing capacity of safety devices                           | Load bearing capacity of safety devices                                                                        | NPD                                               |
| Height and width                                                  | Clear opening height and width in mm                                                                           | Height: Up to 2385 mm<br>Width: Up to 970 mm      |
| Ability to release                                                | Reliable closing of a doorset and/or openable window in the event of fire and/or smoke or power supply failure | NPD                                               |
| Acoustic performance                                              | Sound insulation performance in accordance with EN ISO 717-1                                                   | NPD                                               |
| Thermal transmittance                                             | Thermal transmittance                                                                                          | NPD                                               |
| Radiation properties                                              | Total solar energy transmittance and light transmittance of translucent glazing                                | NPD                                               |
| Air permeability                                                  | Air Permeability                                                                                               | NPD                                               |

\*NPD- Non Performance Declared

TABLE 2. ZA.1 Clauses for fire resistance and/or smoke control doorsets from GUANGDONG YOHOME DOOR CO., LTD.

| Product: Fire resistance and/or smoke control doorsets by the scope of EN 16034.   |                                                                                                                |                                      |
|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|--------------------------------------|
| Intended uses: Fire/smoke compartmentation and on escape routes.                   |                                                                                                                |                                      |
| Essential Characteristics                                                          | Requirement clauses                                                                                            | Results                              |
| Resistance to fire (for fire compartment uses)                                     | Capability to provide “integrity” (E), “integrity and insulation” (EI1, EI2) or “integrity and radiation” (EW) | EI290                                |
| Smoke control (only for applications where limitation of smoke spread is required) | Capability to prevent smoke leakage at ambient (S <sub>a</sub> ) or medium temperature (S <sub>200</sub> )     | S <sub>a</sub> 4<br>S <sub>200</sub> |
| Ability to release                                                                 | Reliable closing of a doorset and/or openable window in the event of fire and/or smoke or power supply failure | NPD                                  |
| Self-closing                                                                       | Ability to close fully without human intervention                                                              | C                                    |
| Durability of self-closing                                                         | Against degradation (cycling testing)                                                                          | 3                                    |
|                                                                                    | Against ageing (corrosion)                                                                                     | achieved                             |

\*NPD- Non Performance Declared

Single Leaf Single Action Swing Wooden Fire Door with Glazed Panel and Wooden Frame.

Fire resistance (Door): max. height 2748.5 mm, max. width 1143.1 mm and max. area 2.851 m<sup>2</sup>.

Smoke control (Door): max. height 2390 mm, max. width 994 mm and max. area 2.376 m<sup>2</sup>.

For detailed information about the doorset and conditions for classification, see Listing Report file (Spec ID: 91664).

END OF DOCUMENT