

Certificate of Compliance



This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

You have been awarded:

Intertek WH US + C Mark for Category C - Proprietary Frames

Standards: CAN / ULC S104 (2015) (R2020), UL 10(b) (2008) (R2020), UL 10(c) (2016) Ed. 3 (R:27 May 2021), NFPA 252 (2022)

Certificate number: WHI24-42597302

Organization: Guangdong Yohome Door Co., Ltd.
Room 2108-1, Floor 21, Building 4, Jiabang Guojin Center
No. 1, Shilong South Road, Guicheng Street, Nanhai District,
Foshan, Guangdong 528299
China

Product: YOHOME - 20 MINUTES WITH HOSE STREAM FIRE
RATED DOOR FRAME (MODEL YH-01)

Spec ID: 77501

Fire Rating: 20 Min PP Category C Proprietary Frame

Listing Information: See following page(s)

Certification body: Intertek Testing Services NA, Inc.

Initial registration: April 10, 2024

Date of expiry: December 31, 2026

Issue status: 3

Authorized By:

A handwritten signature in black ink, appearing to read 'Jean-Philippe Kayl'.

Jean-Philippe Kayl, Director of Certification

Intertek Testing Services NA, Inc.
545 E. Algonquin Road, Ste H., Arlington Heights, IL 60005 USA
Phone: 847-439-5667 Fax: 847-439-7320

www.intertek.com

The certificate and schedule are held in force by regular annual surveillance visits by Intertek Testing Services NA, Inc. and the reader or user should contact Intertek to validate its status. This certificate remains the property of Intertek Testing Services NA, Inc. and must be returned to them on demand. This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

LISTING INFORMATION

FIRE DOOR FRAMES

Wooden Composite CATEGORY C - PROPRIETARY FRAMES for installation in 20 Min masonry or aerated concrete wall openings.

PRODUCT COVERED

YOHOME 20 Minute Fire Rated Wooden Composite Door Frame
Model: YH-01

For use with YOHOME 20 Minute Single Swing Wooden Composite Door.

PRODUCT DESCRIPTION

Frame type: Wooden Composite CATEGORY C - PROPRIETARY FRAMES

Frame stop: 20 mm high at header and jamb edges

Overall Frame Size (Single Swing):

Maximum Width: 1100 mm

Maximum Height: 2450 mm

Minimum Depth: 110 mm

Maximum Door Leaf Size (Single Swing):

Maximum Width: 1024 mm

Maximum Height: 2405 mm

Thickness: 45 mm

Standard Pairs - Not allowed.

Double Egress - Not allowed.

Frames Evaluated to the Following:

Unless otherwise noted, assemblies in this section have been tested to the following standards:

CAN/ULC S104, Standard Method for Fire Tests of Door Assemblies;

NFPA 252, Standard Methods of Fire Tests of Door Assemblies;

UL 10B, Standard for Fire Tests of Door Assemblies;

UL 10C, Standard for Positive Pressure Fire Tests of Door Assemblies;

and are installed, unless otherwise noted, in accordance with the following:

NFPA-80, Standard for Fire Doors and Other Opening Protectives;

Manufacturer's Installation Instructions;

All frames are identified by either a label or embossed marking bearing the wording "Fire Door Frame" and the Intertek WH Certification Mark. Frames rated for less than 3 hours also bear the time interval.